

# Scaime eNod4-T BOX



## **±500 000 d, 1 600 m/s**

- I rustfritt stål IP65-hus
- Godkjent i henhold til OIML R76
- Opptil 8 strain gauge-lastceller
- Feildeteksjonsenhet for lastceller
- Programmerbare digitale filtre
- 2 digitale innganger (4 med IO+-alternativ) og 4 utganger
- Analog utgang 0-10V eller 4-20mA (IO+-alternativ)
- 1 USB-port for innstilling med PC
- Versjon med RS485/CAN PLC-utgang og MODBUS-RTU, CANOpen eller PROFIBUS-DP protokoller
- Versjon med dobbel Ethernet-utgang ad MODBUS-TCP, EtherNet/IP, EtherCAT eller PROFINET-protokoller
- Integrert webserver for overvåking og fjerninnstilling
- Valgfritt integrert eNodTouch-MS/ML berørings-skjermpanel
- Valgfri Bluetooth-kommunikasjon



### **English Description**

## **±500 000 d, 1 600 meas/s**

- Presentation in stainless steel IP65 housing
- Legal metrology certification according to OIML R76
- Up to 8 strain gauge load cells
- Load cells failure detection device
- Programmable digital filters
- 2 digital inputs (4 with IO+ option) and 4 outputs
- Analog output 0-10V or 4-20mA (IO+ option)
- 1 USB port for setting by PC
- Version with RS485/CAN PLC output and MODBUS-RTU, CANOpen or PROFIBUS-DP protocols

- Version with double-Ethernet output ad MODBUS-TCP, EtherNet/IP, EtherCAT or PROFINET protocols
  - Integrated web server for monitoring and remote setting
  - Optional integrated eNodTouch-MS/ML touch screen panel
  - Optional Bluetooth communication
- 

Category: [Indikator/Instrumentering](#), [Scaime](#)

Lager status / Stock Status: instock